

980/1064nm Single Mode Fiber WDM



Product Features


- Low PDL
- Low Insertion Loss
- High Isolation
- High Return Loss
- Stable and Reliable

Product Applications

- Optical Communication System
- Optical Fiber Amplifier
- EDFA Module

Specifications		980/1064 nm	
Parameter	Unit	Premium	A grade
Shorter Wavelength Channel		980±5	
Insertion Loss	Max. dB	0.3	0.4
PDL	Max. dB	0.1	0.15
Isolation @ 1064±5 nm	Min. dB	15	13
Longer Wavelength Channel		1064±5	
Insertion Loss	Max. dB	0.3	0.4
PDL	Max. dB	0.1	0.15
Isolation @ 980±5 nm	Min. dB	15	13
Operating power	Max. W	5	
Operating Temperature	°C	-40 to +85	
Storage Temperature	°C	-50 to +85	
Package Type	mm	S9	Ø3x76: for bare fiber
		S10	Ø3x92: for 0.9mm loose tube
		M3	7.5x18x85: for 0.9mm loose tube or 2mm cable or 3mm cable

Typical Spectrum



Ordering Information

W	D	M			O	O						
Wavelength	Structure	Grade	Package	Fiber Type	Pigtail	Fiber Length	Connector					
C=980/1064nm	1=1x2 2=2x2	P=Premium A=A grade	8=S9 9=S10 F=M3	5=980-20 6=SM1060 7=SM1060 FLEX 8=980-16	S=250µm bare fiber M=0.9mm loose tube L=3mm cable R=2mm cable	0=0.5m 1=0.75m 2=1.0m 3=1.5m 4=2.0m 8=Specify	0=None 1=F/PC 2=F/SPC 3=F/APC 4=SC/SPC 5=SC/APC 6=ST 7=F/UPC 8=SC/UPC 9=MU A=LC B=SC/PC					

Note: 1. Central Wavelength can be customized for different applications.
2. All specifications are before connectors and are subject to change without notice.