

# Star & Tree 50/125μm Multi-Mode Broadband Splitter Module



## Product Features

- Low Insertion Loss
- Low Excess Loss
- High Directivity
- Stable and Reliable

## Product Applications

- Optical Communication System
- LAN
- FDDI
- Access Network

## Specifications

Parameter		Unit	Nx8(N=1,2,8)		Nx16(N=1,2)		Nx32(N=1,2)		
Grade			P	A	P	A	P	A	
Central Wavelength		nm	2000±20 or 1550±20 or 1310±20						
Insertion Loss	Max.	dB	11.5	12.5	15	16	19	20.5	
Excess Loss	Typ.	dB	1.5	2.0	1.5	2.0	2.5	3.0	
Uniformity	Max.	dB	1.5	2.0	2.0	3.0	3.0	3.5	
Central Wavelength		nm	850±20						
Insertion Loss	Max.	dB	13	14	17	18	21.5	23	
Excess Loss	Typ.	dB	2.0	2.5	2.4	3.0	3.0	4.0	
Uniformity	Max.	dB	1.5	2.0	2.0	3.0	3.0	3.5	
Operating power	Max.	W	5						
Operating Temperature		°C	-40 to +85						
Storage Temperature		°C	-50 to +85						
Package Type	mm	M8=43x322x480 M11=58x130x132		M8=43x322x480					
		M5=10x80x100: for 0.9mm loose tube or 3mm cable		M6=18x115x141: for 0.9mm loose tube or 3mm cable					

## Ordering Information

M	B	M																	
Wavelength			Structure			Splitting Ratio		Grade		Package		Fiber Type		Pigtail		Fiber Length		Connector	
4=1550nm 7=1310nm A=850nm P=2000nm S=Specify			18=1x8 28=2x8 88=8x8 A6=1x16 B6=2x16 E2=1x32 F2=2x32			0=Even		P=Premium A=A grade		H=M5 M=M6 K=M8 P=M11		2=50/125μm		M=0.9mm loose tube L=3mm C cable R=2mm C cable F=Adapting Flange		0=0.5m 1=0.75m 2=1.0m 3=1.5m 4=2.0m S=Specify N=None		0=None 1=FC/PC 2=FC/SPC 3=FC/APC 4=SC/SPC 5=SC/APC 6=ST 7=FC/UPC 8=SC/UPC 9=MU A=LC/PC B=SC/PC C=LC/UPC D=LC/APC	

Note: 1. Central Wavelength can be customized for different applications.  
2. All specifications are before connectors and are subject to change without notice.  
3. Measured under the stable mode condition with LED source.