

1x4 Single Mode Dual-Window Broadband Splitter



Product Features


- Low PDL
- Low Insertion Loss
- High Directivity
- Stable and Reliable
- Compact Size

Product Applications

- Optical Communication System
- Optical Testing System
- Optical Fiber Sensor
- Optical Power Distributor

Specifications		Splitting Ratio: 25:25:25:25	
Parameter	Unit	Premium	A grade
Port Configuration		1x4	
Bandwidth	nm	1310±40 and 1550±40	
Insertion Loss	Max. dB	7.5	7.9
Excess Loss	Typ. dB	0.4	0.6
Uniformity	Max. dB	1.4	2.0
PDL	Max. dB	0.25	0.30
Operating power	Max. W	5	
Operating Temperature	°C	-40 to +85	
Storage Temperature	°C	-50 to +85	
Package Type	mm	S11	Ø4x60: for bare fiber
		S12	Ø4x70: for 0.9mm loose tube
		M4	8x26x100: for 0.9mm loose tube or 2mm cable or 3mm cable

Typical Spectrum



Ordering Information

D	B	S								
Wavelength	Structure	Splitting Ratio	Grade	Package	Fiber Type	Pigtail	Fiber Length	Connector		
0=1310&1550nm	4=1x4	25=25:25:25:25	P=Premium A=A grade	A=S11 B=S12 G=M4	1=Ø652 or Equivalent	S=250µm bare fiber M=0.9mm loose tube L=3mm cable R=2mm cable	0=0.5m 1=0.75m 2=1.0m 3=1.5m 4=2.0m S=Specify	0=None 1=F C/PC 2=F C/SPC 3=F C/APC 4=SC/SPC 5=SC/APC 6=ST 7=F C/U/PC 8=SC/U/PC 9=MU A=LC/PC B=SC/PC C=LC/U/PC D=LC/APC		

Note: 1. Central Wavelength can be customized for different applications.
2. All specifications are before connectors and are subject to change without notice.